

In Re: U.S.S.N. 10/035,321

Group Art Unit 2144

Rule 132 Declaration of Sivan, Orell and Krupnik, cont'd

17. Similar correspondences may be pointed out between the apparatus and software product claims in the Application and the subject matter of Appendix A.


We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and conjecture are thought to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application of any patent issued thereon.

\_\_\_\_\_  
Zohar Sivan, Citizen of Israel  
13 Odem Street, Zichron Yaakov, Israel

\_\_\_\_\_  
Date

\_\_\_\_\_  
Dror Orell, Citizen of Israel  
42a Givat Downs Street, Haifa 34349, Israel

\_\_\_\_\_  
Date

  
\_\_\_\_\_  
Hagai Krupnik, Citizen of Israel  
P.O. Box 225, Nofit 36001, Israel

25 Jan 2006  
Date

## APPENDIX A

# HotMedia Streaming Servlet APIs proposal

5 This document contains a draft proposal for APIs for a servlet that will support HotMedia content streaming.

The HotMedia Streaming Servlet will be a standalone module running behind/on top of a standard http server. Hence the only interaction with other HotMedia modules is via URL requests that will be sent from HotMedia applet to the http Server. Therefore, the servlet's functionality is to be defined through the format/syntax of URLs which it should respond to, and the content of the http response.

15 The task of this document is to define this URL syntax. This document does not discuss the changes which are required at the applet side (HotMedia Player) in order to make use of the servlets module. While this does not seem to have impact on the server side it is advised to design the required changes at early stages. (see remark below)

20 The servlet definition in this document applies only to the first phase of introducing servlets to the HotMedia architecture. This phase is restricted to a "Stateless" implementation. The servlet will not use a "session manager", hence no "Back channel" is provided to support real time/online modification of a previous MVR stream request. However some online capabilities can be achieved by means of closing the current MVR file and reopening it with new streaming parameters. The question how to use it within the HotMedia Applet should be addressed elsewhere.

25 If and when a session manager will be added to the servlet module, it will be "backwards compliant". I.e. Previous HotMedia Applet will be able to use the "new" hotMedia Streaming Servlet.

**Document version :** 0.03 July 15 **Servlet Name :** We shall refer to this module as *HotMedia Streaming Servlet*.

### Servlet Module Requirements:

30 The servlet module will be a set of pure java classes. The servlet's "main" class name will be hmServlet.class. The "instalation" of this servlet should be simply to put a set of classes in a predefined location within the servlet-engine directory tree.

The servlet module will have to be tested such that it is working properly across main http servers on several platforms. The test plan will be defined later.

35 Since the servlet has to parse mvr file format it is desirable if the servlet can have a parser which is aligned with the HotMedia Player parser (see remark below)

## Servlet URL calls :

To retrieve mvr stream via hmServlet, the URL that will be sent from hmMaster will be of the following Syntax :

`http://hostname/servlet/hmServlet/mvrFilePath?queryString`

5                where :

- The red part is fixed and hard coded
- hostname is the name of the web server

10                mvrFilePath is the path to the mvr file including its filename + extension and excluding the root  
E.g. if an mvr file can be downloaded from an http server (without servlet support) using the URL :

`http://MyWebServer/MyContentPath/MyMvrFile.mvr`  
than the servlet URL request will be :

15                `http://MyWebServer/servlet/hmServlet/MyContentPath/MyMvrFile.mvr?queryString`

- queryString is a string which uses standard SQL format as described below.
- Due to servers inconsistencies - all queries are assumed to be case sensitive.
- calling `http://hostname/servlet/hmServlet/` without MVR filePath will be used for remote debugging.

25                Using such a call directly from the URL window of a browser will create a text/html file response with various variables that will be helpful for debugging (hotMediaServlet version, some data on the server machine).

- Calling `http://hostname/servlet/hmServlet/mvrFilePath` without a query string will be used for debugging as well.

35                In this case the mvr file will be sent to the client "as is", hence the servlet will serve as an "Identity filter".  
This feature can be used later on as a performance checker to verify that the increase of delay & servers CPU consumption due to servlet module is minimal.

40                The http response for these request will be of mime type *"application/octet-stream"*. This type is "basic" and works well when an applet tries to read binaries input stream from an http server. To our best knowledge, this detail has no effect on any other component in the framework. (I.e. nothing has to be configured to support this).

## Servlet queryString :

The servlet queryString is of the following format :

servletAction=action1/&servletAction=action&param1=value1/&param2=value2

5                where :

- All sub strings action<sub>i</sub>, param<sub>i</sub> & value<sub>i</sub> should be URL encoded prior to concatenation (see [sample code](#))
- [servletAction\(s\)](#) are the name of the actions that the servlet is requested to perform. Typically only one action will be used per call. However this is not mandatory (see details below).

10

=> If no action is selected the query string will be null and the mvr file will be sent to the client "as-is".

15

=> some actions can not be performed simultaneously while some do not (see details below)

- param<sub>i</sub> is the name of the i'th\* parameter that is required in order to perform the action (see details below)

\* The parameters can be ordered arbitrarily.

20

- value<sub>i</sub> is the value of the i'th\* parameter that is required in order to perform the action (see details below)

\* The parameters can be ordered arbitrarily.

25

- There is a delimiter "&" between each parameter/value pair
- No spaces will be present in any of the actions/parameters/values unless they are strings which are taken from the mvr headres. In this case - theservlet will support whatever hotMedia applet support.

## Suggested Servlet list of action :

30

1. [startAtByte](#)
2. [selectTime](#)
3. [selectTracks](#)
4. [skipTracks](#)
5. [selectMediaType](#)
6. [skipMediaType](#)
7. [FitToBandwidth](#)
8. [limitStreamSpeed](#)
9. [getZoomedImage](#)

35

10. and up - TBD

**Note :** Not all of the above will be implemented in the coming HotMediaTurbo Beta release.

5

For each action we now specify the parameters that can be used and a list of actions that can not be handled in a single URL request (prohibited simultaneous Actions).

- 10
1. **startAtByte** - this action is a "dumb" servlet action which simply start streaming from an arbitrarily requested byte within the MVR file. It is the duty of the hmApplet (hmMaster?) to calculate the start point for the servlet stream and to handle the coming stream accordingly. The output is **not** a valid mvr stream.

15

**parameters :** startByte=intValue where intValue is a string that represent a non-negative integer which is the location of the first byte within the MVR file.

**prohibited simultaneous Actions :** selectTracks, skipTracks selectMedia, skipMedia, FitToBandwidth,

20

**output :** A bitstream that makes sense only to the sender since it starts from an arbitrary point within the

- 25
2. **selectTime** - this action will start streaming from an arbitrarily requested time within a specific track within the MVR file. The output is a valid mvr stream which holds only portion of the track that is selected via the parameters.

Note that it might be suitable to call the hmPlayer startOfData() following the URL request of this action.

30

**parameters :** trackId=trackIdValue where trackIdValue is a string that represent the trackId to be selected  
startTime=intValue where intValue is a string that represent a non-negative integer which represents the requested time in msec from which the servlet should stream this track.

35

**Note :** if startTime parameter is missing from the Query string the servlet will send the bitstream from the beginning of the selected track

endTime=intValue where intValue is a string that represent a non-negative integer which represents the requested time in msec from which the servlet should stop streaming this track.

40

**Note :** if endTime parameter is missing from the Query string the servlet will send the bitstream till the end of this track

**prohibited simultaneous Actions :** selectTracks, skipTracks selectMedia, skipMedia,

- 5      3. **output :** The output is a valid mvr stream which adjust all its headers to correctly define the selected portion of the selected track.

10

4. **selectTracks** - This action specifically selects the tracks that should be streamed to the client. all other tracks are skipped.

15

**parameters :** trackId=trackIdValue where trackIdValue is a string that represent the trackId to be selected

- 20      Note : there could be several <trackId=trackIdValue > pairs in a single servlet call.

**prohibited simultaneous Actions :** skipTracks, selectMediaType, skipMediaType, startAtByte

- 25      **output :** A valid mvr stream which is a subset of the original mvr file.

5. **skipTracks** - This action selects the tracks that should be skipped when the mvr file is streamed to the client. All other tracks are sent by their order.

30      **parameters :** trackId=trackIdValue where trackIdValue is a string that represent the trackId to be selected

Note : there could be several <trackId=trackIdValue > pairs in a single servlet call.

**prohibited simultaneous Actions :** selectTracks, selectMediaType, skipMediaType, startAtByte

- 35      **output :** A valid mvr stream which is a subset of the original mvr file.

6. **selectMediaType** - This action selects the tracks that corresponds to a specific media type and stream them to the client. All other tracks are skipped.

5

**parameters** : MediaType=MediaTypeString where MediaTypeString is a string that represent a hotMedia valid MediaType

Note : there could be several <MediaType=MediaTypeString> pairs in a single servlet call

10

**prohibited simultaneous Actions** : selectTracks, skipTracks, skipMediaType, startAtByte

**output** : A valid mvr stream which is a subset of the original mvr file.

15

7. **skipMediaType** - This action selects the tracks that should be skipped when the mvr file is streamed to the client. All other tracks are sent by their order.

20 **parameters** : MediaType=MediaTypeString where MediaTypeString is a string that represent a HotMedia valid MediaType

Note : there could be several <MediaType=MediaTypeString> pairs in a single servlet call.

**prohibited simultaneous Actions** : selectTracks, skipTracks, selectMediaType, startAtByte

25

**output** : A valid mvr stream which is a subset of the original mvr file.

8. **FitToBandwidth** - This is a recommendation to the servlet to fit the MVR representation to a specific bandwidth. The discussion of how will the server use it is postponed to the future (and so are the parameters).

30

**parameters** : TBD

**prohibited simultaneous Actions** : startAtByte (may be others as well TBD)

35

**output** : A valid mvr stream which is a subset of the original mvr file.

9. **limitStreamSpeed** - This action recommends to the server to send the stream at a speed no faster than a specified speed.

5 Typically an http server streams the data As fast as possible. However when the client sends several requests symultanously (such as request for classes, request for other html pages etc...) and the client's bandwidth is limited it might be desirable to limit the speed of the mvr streaming. This action is provided in order to leave enough bandwidth to other streams that the client opens such as streams to get classes and plain http streams. The output stream content is not changed by this action

10 Note : At this stage we shell consider this action as exploratory since more has to be done to verify that the client can really benefit from such approach.

**parameters** : streamSpeed=intValueSpeed where intValueSpeed is a string representation of an integer value which is the preferred speed in kBit/sec

15 **prohibited simultaneous Actions** : none

**output** : The output stream content is not changed by this action

- 20 10. **getZoomedImage** - This action provides an interface to high resolution ZoomView of a given Image.

In this implementation it is assumed that :

25 => There are two initial images with the same content in different resolution denoted *inline image* and *High resolution image*

=> The two images are of the same aspect-ratio (width/height) up to some rounding error.

30 => The client/applet has the capabilities to display the *inline image* as a whole, and then mark a portion of the image of which the user would like to magnify. The look and feel (GUI) of the portion selection is irrelevant to the request as long as the applet is able to describe the selected portion using the parameters described below.

35 The servlet calculates which portion of the high Resolution it should crop, and how much to down scale it such that the result will have identical range to the inline image crop and identical size to the whole inline image

**parameters** :

inlineWidth=intValueString - The width (in pixels) of the *Inline Image* to be magnified

40 inlineHeight=intValueString - The height (in pixels) of the *Inline Image* to be magnified

width=intValueString - The width (in pixels) of the selected portion of the *Inline Image* to be magnified



height=intValueString - The height (in pixels) of the selected  
 portion of the Inline Image to be magnified  
 x=intValueString - The x coordinate (in pixels) of the upper  
 left corner of the selected portion of the Inline Image to be magnified  
 5 y=intValueString - The y coordinate (in pixels) of the upper  
 left corner of the selected portion of the Inline Image to be magnified  
 imagePath=FileString - A path to either a high resolution  
 JPEG image or an MVR file which includes such high-resolution Image.  
 10 trackId=trackIdString - Used only if If the High resolution Image  
 is within an MVR file. The trackId of the *High resolution image*

Note : If we will need to fetch the high-resolution images from  
 a Database the imagePath parameter will have to be generalize to support  
 the needed info for fetching images from the DataBase. However the issue of  
 handling images that are stored in databases is beyond the scope of this  
 15 document.

**prohibited simultaneous Actions :** selectTracks, skipTracks,  
 selectMediaType, skipMediaType, startAtByte,

**output :** The output stream content is either an MVR stream which has a  
 single media track holding a JPEG image, or a "stripped" JPEG stream (issue  
 20 TBD)

The dimension of the output image is inline WidthXinlineHeight  
 pixels

## 25 **Error handling :**

When a servlet parses a request it might find out that it can not execute the request.  
 Reasons for this may vary:

- MVR File can not be read (absent/permissions etc...)
- queryString is not valid/can not be handled.
- 30 • MVR file has bugs/unsupported features etc....
- runtime errors (outOfMemory, bad connection etc ...)

In terms of error handling, the errors in the servlet can be separated into two types of  
 errors :

1. Errors that the servlet identifies before it starts streaming data to the client.
  - 35 2. Errors that occur during the servlet's streaming.
1. In the first case the server can signal the problem to the applet using the http  
 header fields.  
 For example the httpResponseCode could be changed from the typical 200 to  
 some redefined code number. This can be detected by the applet using  
 40 URLConnection.getHeaderField(...). Moreover - in this case the servlet can  
 stream an html/text file which describe the problem .... (useful for debugging)

2. In the second case - the only thing that the servlet can do is to close the output stream. This, in turn will cause an exception in the applet.

#### Additional remarks :

- 5 1. We have to analyze the changes needed to be done in the client side at an early stage and make sure that the described URL calls :
  - o calls can serve HotMedia applet properly.

For example : For each request we have to ask were can we fire such a request from the current/modified HotMedia Applet

- 10 o can be created easily within HotMedia Player ?

For example : For each request we have to ask ourselves how will hotmedia be capable to create the needed parameters for the required action(s).

- 15 2. Can we have an mvr parser class that will be common to the applet and the servlet ? Currently the parser is part of hmMasket and it is not trivial to separate its source from the rest of the java file.

#### A code example :

20

Here is a sample (pseudo) code that should be integrated into the applet in order to create a URL request to the HotMedia Streaming Servlet

Note : This pseudo code has not been compiled and (naturally) not tried as a standalone. Therefore it is not guarantied to be bug free ...

25

```
String ServletAction[] = .....
String param[] = .....
String value[] = .....
URL mvrURL = new
30 URL("http://myHost/myContentPath/myMvrFile.mvr");
// .....
// absolute & complete URL definition
String servletPath =
mvrURL.getProtocol()+mvrURL.getHost()+"servlet/hmServlet/"+mvrU
35 RL.getFile();
String queryString="?";
queryString+= URLEncoder.encode("servletAction") +"="
+URLEncoder.encode(ServletAction[i]);
for(.....) {
40   queryString+= "&"+ URLEncoder.encode("servletAction") +"="
+URLEncoder.encode(ServletAction[i]);
}
for(.....) {
```

```

        queryString+="&" + URLEncoder.encode(param[i]) +"="
+URLEncoder.encode(value[i]);
    }
    URL url = new URL(servletPath+queryString);
5    urlc = url.openConnection();
    urlc.setUseCaches(false);    // All servlet calls should not be cached in
    the browser cache.
    dis = new DataInputStream(urlc.getInputStream());
    //
10    // from here on one can use the dis as if it is a regular dis
    from an http response.

```

---

*Comments, suggestions and discussions are more than welcomed :*

15     *Hagai Krupnik*  
        *Audio/Video Group - Multimedia Technologies*  
        *IBM Research Laboratory in Haifa, Israel.*  
        *LotusNotes : Hagai Krupnik/Haifa/IBM@IBMIL@IBMHAIFA*

20     *Phone     : +972-4-8296436*  
        *Fax       : +972-4-8296112*  
        *snail Mail : MATAM Haifa 31905 ISRAEL.*  
        *Email : hagai@il.ibm.com*

## APPENDIX B

Hagai  
Krupnik/Haifa/IBM

19:20 15/07/1999

To

Jeane Chen/Watson/IBM@IBMUS  
Keeranoor Kumar/Watson/IBM@IBMUS ,  
Robert Plotkin/Watson/IBM@IBMUS ,  
Subrina Chang/Watson/IBM@IBMUS ,  
Liang-Jie Zhang/Watson/IBM@IBMUS ,  
James Lipscomb/Watson/IBM@IBMUS ,  
Peter Westerink/Watson/IBM@IBMUS ,  
Ed Snible/Watson/IBM@IBMUS, Gabriel  
Taubin/Watson/IBM@IBMUS, Yun  
Deng/China/IBM@IBMCN, William  
Gaddy/Watson/Contr/IBM@IBMUS

cc

Gilad Cohen/Haifa/IBM@IBMIL, Ehud  
Karnin/Haifa/IBM@IBMIL@IBMDE, Zohar  
Sivan/Haifa/IBM@IBMIL

Subject

HotMedia Streaming Servlet APIs  
proposal

Hi all

It's been two weeks since our summit meeting. Personally I've enjoyed the meeting and it was nice to meet in person people I've only recognize by their notes header.

Anyway, now we're back to business and there is a "Architecture complete deadline" in two weeks from now. So....

I have just posted our proposal for HotMedia Streaming Servlet APIs to the HotMedia discussion database. It is very important that we'll get a serious feedback on it. Even though, I can guess; most of you are busy with other aspects of HotMedia/HotMediaTurbo. I just want to make sure that the designed servlet is really useable for HotMedia applet, otherwise we should alter the definition before we get into coding. If there is anyone who can't access this database, please let me know and I'll mail him/her the file directly.

looking forwards to hear your comments/suggestions

Hagai Krupnik  
Audio/Video Group - Multimedia Technologies  
IBM Research Laboratory in Haifa, Israel.

LotusNotes : Hagai Krupnik/Haifa/IBM@IBMIL@IBMHAIFA  
Email : hagai @ il.ibm.com  
Phone : +972-4-8296436  
Fax : +972-4-8296112  
snail Mail : MATAM Haifa 31905 ISRAEL.

## APPENDIX C

-Forwarded by Hagai Krupnik/Haifa/IBM on 07/20/99  
09:41AM-----

To: Hagai Krupnik/Haifa/IBM@IBMIL@IBMDE  
cc: Jeane Chen/Watson/IBM@IBMUS  
From: Subrina Chang/Watson/IBM@IBMUS  
Subject: Re: HotMedia Streaming Servlet APIs proposal (Document link:  
Hagai Krupnik(

Hagai,  
Thanks for your effort to come up this document. We will need some time to  
review your proposal. We will get back to you as soon as possible.

Subrina

-----  
Subrina Chang  
IBM - Internet Media Group  
Tel: 914-784-5756 TieLine: 863-5756  
e-mail: [subrina@us.ibm.com](mailto:subrina@us.ibm.com)

## APPENDIX D

-Subrina  
Chang/Watson/IBM  
IBMUS

@

To

Hagai Krupnik/Haifa/IBM@IBMIL@IBMDE

21:20 26/07/1999 cc

Jeane Chen/Watson/IBM@IBMUS, Gilad

Cohen/Haifa/IBM@IBMIL@IBMDE, Zohar

Sivan/Haifa/IBM@IBMIL@IBMDE

Keeranoor Kumar/Watson/IBM@IBMUS

Subject

Re: HotMedia Streaming Servlet APIs

proposal(Document link: Zohar Sivan

Archive

((

Hagai,

In addition to those servlet actions proposed in your documentation, I like to introduce more parameters to "startAtByte". Currently, only one parameter defined for this servlet action - "startByte", an offset to the MVR file. It may be very straight forward but may not be practical for any media player. It's hard for a media player to come up with an accurate offset including header frame and any previous media frames. The following parameters proposed will give "startAtByte" more flexibility:

(1)startTime - Instead of a byte offset, a time offset is given if a specific media track can be measured by time.

(2)trackID - If "trackID" is specified, the offset specified in either "startByte" or "startTime" is only within this specific media track. We can impose "startTime" to be used with "trackID" in pairs. Only "startByte" can be left alone. Without any specific track defined, "startByte" interprets an offset within an entire MVR stream.

As for a common parser for both hmmaster and servlet, it is really nice to have but not "practical" for HotMedia. There will be one more class file to be downloaded for HotMedia player. At least, current implementation of mvr file parser in hmmaster is written in procedures (several functions). It won't be too difficult to extract them out. Steve Wood in Juerg's area is the author of hmmaster and also can answer any possible questions in terms of mvr file parser in details.

Subrina

-----  
Subrina Chang

IBM - Internet Media Group

Tel: 914-784-5756 TieLine: 863-5756

e-mail: [subrina@us.ibm.com](mailto:subrina@us.ibm.com)

## APPENDIX E

Keeranoor Kumar@IBMUS  
09:49 07/28/99PM

To: Arun Ramchandra@Ibmus, Ross Leung/Watson/Ibm@Ibmus, Robert Plotkin/Watson/Ibm@Ibmus, Subrina Chang/Watson/Ibm@Ibmus, Liang-Jie Zhang/Watson/Ibm@Ibmus, James Lipscomb/Watson/Ibm@Ibmus, Michelle Y Kim/Watson/Ibm@Ibmus, Peter Westerink/Watson/Ibm@Ibmus, Steve Wood/Watson/Ibm@Ibmus, Jeff Boston/Watson/Ibm@Ibmus, Ed Snible/Watson/Ibm@Ibmus, Ehud Karnin/Haifa/Ibm@Ibmil@Ibmde, Leo Y Liu/China/Ibm@Ibmcn, Dong Xie/China/Ibm@Ibmcn, Gabriel Taubin/Watson/Ibm@Ibmus, Andre Gueziec/Watson/Ibm@Ibmus, Hagai Krupnik/Haifa/Ibm@Ibmil, Yun Deng/China/Ibm@Ibmcn, Peter Schirling/Burlington/Ibm@Ibmus, Zohar Sivan/Haifa/Ibm@Ibmil, Joshua Mittleman/Watson/IBM@IBMUS

cc: Jeane Chen/Watson/IBM@IBMUS, Juerg von Kaenel/Watson/IBM@IBMUS, Jai Menon/Watson/Ibm@Ibmus, William Pence/Watson/Ibm@Ibmus

From: Keeranoor Kumar/Watson/IBM @ IBMUS

Subject: HotMedia Turbo Development Plan (Document link: Hagai Krupnik(

Folks,

As some of you know already, I have been asked to oversee the execution of the HotMedia Turbo development plan. It is a privilege to be working with such a wonderful and talented team and I am excited. Looking at the chart that was created at the end of the recent summit, I see 7/30 as the day to finalize the architecture and 9/30 to build the first function prototype. Clearly, we need to come up with a much more detailed plan. As a first step, I am proposing a list of tasks below and some names against each of them. I welcome your input on the assignment of names and also on whether you see more task items. Please note that participation in each task is absolutely open. Please send this ASAP as we should close this list by end of 7/29 say. The step after that would be to come up with a much more detailed breakdown for each item and attach a date with them.

Architecture - steve wood, kumar

Extension of Extensions API for the new media types - steve wood, liang-jie, juerg, kumar

File format extensions for new media types - peter westerink, jim lipscomb, subrina, kumar

Video - hagai, zohar, subrina

3 D - josh, gabriel, jim lipscomb

MPEG4 - peter westerink, steve wood

Stateless Servlet for Content selection - hagai, zohar, subrina, liang-jie, kumar

File format extensions for servlet actions - hagai, zohar, kumar

Servlet API for client interaction - hagai, zohar, subrina, liang-jie

Servlet design - hagai, zohar

Authoring extensions for new media types-



- Video - hagai, zohar, yun deng
- 3 D - josh, gabriel
- Authoring tool for MPEG4 - steve wood, peter westerink
- Implementation
- Media Objects
- Video - hagai, zohar, yun deng
- 3 D - josh
- MPEG4 - steve wood, peter westerink
- Authoring Extensions
- Video - hagai, zohar, yun deng
- 3 D - josh
- MPEG4 Authoring Tool (producing an mvr file) - steve wood
- Main Applet & Master Extensions (if any) - steve wood
- Action Handler Extensions - ed snible
- Servlet - hagai, zohar
- Unit Test - - ed snible (authority for acceptance for integration)
- Media Objects
- Video - hagai, zohar, yun deng
- 3 D - josh
- MPEG4 - steve wood, peter westerink
- Authoring Extensions
- Video - hagai, zohar, yun deng
- 3 D - josh
- MPEG4 Authoring Tool
- Mail Applet, Master Extensions & Hyperlinking - steve wood, ed snible
- Servlet - hagai, zohar
- Documentation
- Integration
- Authoring Components - ed snible
- Client Components - ed snible
- Installation Package - ed snible
- System Test
- Test Plan Generation - ed snible, kumar, vee savath
- Test - vee savath's team

Please send your response if any ASAP.

Thanks.

-Kumar